

TDL8 Downlight

8" Low Profile Series

Schedule ID	
Part Number	
Notes	



Low profile 8 inch fixture.
Recessed lighting with **no housing required.**

Product Description

This fully dimmable low-voltage LED fixture is Airtight certified (in accordance with ASTM E283) and is rated for insulation contact (IC) and wet locations. This Class 2 solution contains no electronics in the fixture. The dimming control, power conversion and constant current drivers for multiple fixtures are housed in a remote DC, Class 2 intelligent power supply, which can be located up to 150' away from the fixtures.

Ideal applications: hospitality, retail, commercial, architectural lighting

Performance Summary

Light Output	465 - 1380 lumens
CCT	2700K, 3000K, 3500K, 4000K*, 5000K*
CRI	90+ (2700K, 3000K)
Drive Current	350 mA - 1000 mA
Forward Voltage	18 Vf max
L70 Lifetime	50,000+ hours
Beam Angle	110°
Warranty	5-year limited warranty
Dimming	Dimmable to 0.2%

*Please consult with your LumaStream account manager for pricing and lead times.

Ordering Information Example: TDL8R-30W

TDL8		-	
Base	Shape	CCT	Finish
TDL8	R Round	27 2700K (std) 30 3000K (std) 35 3500K (std) 40 4000K* (opt) 50 5000K*(opt)	W White

TDL8 Downlight Specifications

Light Output

Drive Current	CCT	Lumens	Voltage	Watts	Fixtures/Ch	Fixtures/PS	CRI	Compatible Power Supplies
350 mA	3000K	465	18	6.3	2	24	90+	70-12-0350-XXX-XX
450 mA	3000K	592	18	8.1	2	24	90+	70-12-0450-XXX-XX
500 mA	3000K	660	18	9	2	18	90+	70-09-0500-XXX-XX
700 mA	3000K	952	18.6	13	2	16	90+	70-08-0700-XXX-XX
700 mA	3000K	952	18.6	13	2	12	90+	70-06-0700-XXX-XX
700 mA	3000K	952	18.6	13	1	12	90+	66-12-0700-XXX-XX
1000 mA	3000K	1380	18.7	19	1	9	90+	66-09-1000-XXX-XX

**For 4000K lumen values multiply 1.07

Construction & Materials

Dimensions Round/Square	8 ¾" D x 1 5/16" H
Weight	0.5 lbs
Material	Die Cast Aluminum, Polycarbonate Diffuser
Operating Temperature	0°C to 40°C / 4°F to 104°F
Mounting Options	Recessed
Ceiling Cutout-Round	8 ¼" Ceiling Hole Cutout

Certifications & Qualifications

TUV Certified to UL 1598	Yes
IC Rated	Yes
AT Rated	Yes
Suitable for Wet Locations	Yes
RoHS Compliant	Yes

For more information, please contact:

+1 (727) 827-2805

sales@lumastream.com

LumaStream, Inc. reserves the right to make changes without further notice to any products herein to improve reliability, function, or design. LumaStream does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.

LS0218 / TDL6 Downlight



Rev: 5/22/2018