


Schedule ID	
Part Number	
Notes	

Quadrallux EP24

2'x4' Grid-Mount Edgelit Flat Panel



Product Description

This Quadrallux EP24 is an ultra low profile 2'x4' fixture that can be recessed into standard grid ceilings or cable hung from a ceiling. The Quadrallux EP24 provides uniform illumination that maximizes visual comfort and efficiency. The fixture is only .5" in depth and will lay into a standard t-style grid ceiling. Integral seismic clips can secure the fixture to grid ceiling.

The dimming control, power conversion, and constant current drivers for multiple fixtures are housed in a remote DC, Class 2 intelligent power supply, which can be located up to 150' away from the fixture.

Ideal applications: hospitality, retail, commercial, architectural lighting

Performance Summary

Light Output	2455 - 4910 lumens
CCT	3000K*, 3500K, 4000K, 5000K*
CRI	80+ Standard, 90+ Optional*
Drive Current	350 mA - 700 mA
Forward Voltage	32.3 Vf max
Beam Angle	110°
L70 Lifetime	TM-21 calculated 36,000
L70 Lifetime	TM-21 projected 160,000
L90 Lifetime	TM-21 projected 50,000
Warranty	5-year limited warranty
Dimming	Dimmable to 0.2%

*Please consult with your LumaStream account manager for pricing and lead times.

Ordering Information Example: EP24-40-SM-W

Base	CCT	Mount	Finish	CRI
EP24 - Standard Output	30 3000K* (opt) 35 3500K (std) 40 4000K (std) 50 5000K* (opt)	RM Recessed Mount SM Surface Mount	W White	- 80 (Default Standard Option, Leave Blank) 9 90*

Quadrallux EP24 Flat Panel Specifications

Standard Configuration

Drive Current	CCT	Lumens	Voltage	Watts	Fixtures/Ch	Fixtures/PS	CRI	Compatible Power Supplies
350 mA	3500K	2455	32.3	11	0.5	6	80+	70-12-0350-XXX-XX
450 mA	3500K	3201	32.3	15	0.5	6	80+	70-12-0450-XXX-XX
500 mA	3500K	3414	32.3	16	0.5	4	80+	70-09-0500-XXX-XX
700 mA	3500K	4910	32.3	23	0.5	4	80+	70-08-0700-XXX-XX
700 mA	3500K	4910	32.3	23	0.5	3	80+	70-06-0700-XXX-XX

*For 3000K multiply by .94, 4000K by 1.03, 5000K by 1.07


Construction & Materials

Dimensions	23.75" x 47.70" x .5"
Weight	12.6 lbs
Material	Aluminum, Polycarbonate Diffuser
Operating Temperature	0°C to 40°C / 4°F to 104°F

Certifications & Qualifications

TUV Certified to UL 1598	Yes
IC Rated	Yes
Suitable for Wet Locations	Yes
RoHS Compliant	Yes

Mechanical Dimensions



For more information, please contact:
 +1 (727) 827-2805
 sales@lumastream.com

LumaStream, Inc. reserves the right to make changes without further notice to any products herein to improve reliability, function, or design. LumaStream does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.

Quadrallux EP24 Flat Panel



Rev: 12/14/2018